

testo 106

The core thermometer testo 106 with a thin, robust measuring tip, excellently suited for fast core temperature monitoring in gastronomy, in hotels, large kitchens, supermarkets etc.

testo 106, core thermometer incl. probe protecting cap and battery

Part no.
0560 1063

The Compact Food Thermometer With Alarm

- TopSafe (optionally or in a set), waterproof and dishwasher-safe protective case (IP 67)
- Fast measurement (2 measurements per second)
- Almost invisible penetration hole due to special food probe
- Small, handy and always close to hand
- Automatic recognition of final value (Auto-Hold)



Only in combination with TopSafe



Technical data

Meas. range	-50 to +275 °C
Accuracy	±1 % of mv (+100 to +275 °C)
±1 digit	±0.5 °C (-30 to +99.9 °C) ±1 °C (-50 to -30.1 °C)
Resolution	0.1 °C
Oper. temp.	-20 to +50 °C
Storage temp.	-40 to +70 °C
t ₉₉	10 s
Battery type	3V button cell (CR 2032)
Battery life	350 h
Dimensions	215 x 34 x 19 mm
Display	LCD, 1 line
Material/Housing	ABS
Weight	80 g
Protection class	IP 67 with TopSafe
Warranty	2 years

Set

Set testo 106, core thermometer incl. TopSafe (waterproof protective case, IP 67), belt clip, probe protecting cover and battery

Part no.

0563 1063

Accessories

Frozen food drill; loss-proof attachment to belt clip

Part no.

0554 0826

TopSafe (indestructible protection case); waterproof and dishwasher-safe protection case (IP67)

0516 8265

Holding clip with probe protection cap

0554 0825

Accessories

ISO calibration certificate/temperature ; for air/immersion probes, calibration point +60°C

Part no.

0520 0063

ISO calibration certificate/temperature ; for air/immersion probes, calibration point -18°C

0520 0061

ISO calibration certificate/temperature ; for air/immersion probes, calibration point 0°C

0520 0062

ISO calibration certificate/temperature ; for air/immersion probes, calibration points -18°C; 0°C

0520 0041

ISO calibration certificate/temperature ; for air/immersion probes, calibration points -8°C; 0°C; +40°C

0520 0181